

Light Weight Shirt

COMMERCIAL IN CONFIDENCE

RM208V2R Ladies 2 Tone Vented Light Wt Open Front Long Sleeve Shirt with Reflective Tape







Features

- Twin Needle Stitching and Bar-tacks for Extra Strength
- Cotton Mesh Cooling Vents Located at Underarm and Shoulder Positions
- Garments with Sleeves Comply with AS 4399:2020 Standard for UPF50+
- AS/NZS 4602.1:2011 and AS/NZS 1906:4:2023 for High Visibility Day/Night Wear
- Blue is not High Visibility Colour, for Night Use only When Reflective Tape is Applied

Fabric

Cotton Twill, 150gsm Light Weight

Colour

Orange-Navy Yellow-Navy Blue-Navy





Yellow-Navy

Blue-Navy

| Mesh Ventilation | | /entilation | Cotton Mesh | | | | | | | |
|-------------------------|---|-------------|-------------|---|-----------|--|--|--|--|--|
| | X | Underarm | Gusset | X | Back Yoke | | | | | |

Tape ConfigurationReflective Tape 50mmFront Body:2 hoops horizontalBack Body:2 hoops horizontal

Arms: 1 hoop

Hi Visibility Application

X Day time X Night time

Blue is not High Visibility Colour, for Night Use only When Reflective Tape is Applied

Size Range

6 - 20

Fabric Quality

| rabile Quality | | | | | |
|-------------------|--------------------------|------------|--|--|--|
| Dimension Stabili | +/-3% | | | | |
| Colour Fastness | Colour Change | 4 | | | |
| to Washing | Colour Staining | 4-5 | | | |
| Colour Fastness | Dry | 3-4 | | | |
| to Rubbing | Wet | 2-3 | | | |
| Colour Fastness t | Colour Fastness to Light | | | | |
| Tearing | Warp | >=15 min N | | | |
| Strength | Weft | >=12 min N | | | |
| UPF (AS 4399:20 | 50+ | | | | |

Measurement Table

| mododi omont i dolo | | | | | | | | | | |
|---------------------|----|------|----|---------|-----------|---------|----|------|--|--|
| Major Points | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | | |
| 1/2 Chest | 48 | 50.5 | 53 | 55.5 | 58 | 62 | 66 | 70 | | |
| Centre Back Length | 76 | 77 | 78 | 79 | 80 | 81 | 82 | 83 | | |
| Sleeve Length | 41 | 42 | 43 | 44.5 | 45.5 | 47.5 | 49 | 50.5 | | |
| Shoulder Width | 59 | 59 | 60 | 61 | 61 | 62 | 63 | 64 | | |
| Pocket Dimension | • | | • | \\/idth | 12 v Dent | h 1/1cm | | | | |

